

DATA SHEET: BZ325003



SCHRACK-INFO

- Rail Mountable socket with LED light indicator and screw connection
- Housing color: gray
- RoHS according
- National version: Germany
- Housing width 45mm

TECHNICAL DATA

GENERAL

Nominal voltage Un:	250V AC
Nominal current In:	16A AC
Status display:	green LED with preresistor
Contact material:	CuZn37
For country specific use in:	D
Color:	gray RAL 7035
insulating material:	PA66, UL94 V O
Ambient temperature:	20°C 60°C
Standards/regulations:	Directive 2006/95/EG
	DIN 49440 I
	DIN VDE 0620 1:201002

DIMENSIONS

Length x Width x Height:	75 x 45 x max. 65 mm
--------------------------	----------------------

TYPE OF CONNECTION

	Screw connection with protection against accidental contact, all three mains connection clips are arranged on the bottomside
--	--

Connection data	
Conductor cross section solid min:	0,2 mm ²
Conductor cross section solid max:	4 mm ²
Conductor cross section stranded min:	0,2 mm ²
Conductor cross section stranded max:	2,5 mm ²
Conductor cross section AWG/kcmil min:	24
Conductor cross section aWG/kcmil max:	12
Stripping length:	8mm
Screw thread:	M3
Mounting:	DIN rail according to EN60715
Fixing hook:	metal, marking tag
CERTIFICATES	VDE Certificate No. 40029547, CE

DESCRIPTION	ORDERNUMBER
Rail mountable socket with LED and screw connection	BZ325003